


UKCA marking information – Colas Ltd

| | |
|---|--|
|  0836 | |
| Colas Ltd, 6210 Bishops Court, Birmingham Business Park Solihull, Birmingham B37 7YB 13 C3 UK 0836-CPR-13/F035 | |
| <i>BS EN 13808</i> <i>Cationic bituminous emulsion</i> <i>SLX-80 C69BPF2/3/4 C70BPF2/3/4</i> <i>intended to be used for surface treatment as surface dressings</i> | |
| EMULSION | |
| <ul style="list-style-type: none"> • Efflux 4 mm at 40°C - EN 12846-1 • Water effect on binder adhesion – EN 13614 • Breaking behaviour – EN 13075-1 | 5-100 s (Class 5/6) ≥ 90 (Class 3) <110-195 (Class 2/3/4) |
| RECOVERED BINDER | |
| <ul style="list-style-type: none"> • Penetration at 25°C - EN 1426 • Softening point – EN 1427 • Cohesion by pendulum – EN 13588 | ≤ 220 (Class 5) ≥ 43°C (Class 6) ≥ 1.2 J/cm ² (Class 3) |
| STAGE 1 DURABILITY - STABILISED BINDER | |
| <ul style="list-style-type: none"> • Durability of penetration at 25°C – EN 1426 • Durability of softening point – EN 1427 • Durability of cohesion by pendulum – EN 13588 | NPD NPD NPD |
| STAGE 2 DURABILITY - AGED BINDER | |
| <ul style="list-style-type: none"> • Durability of penetration at 25°C – EN 1426 • Durability of softening point – EN 1427 • Durability of cohesion by pendulum – EN 13588 | ≤ 220 (Class 5) ≥ 43°C (Class 6) ≥ 0.7 J/cm ² (Class 5) |
| Dangerous regulated substances | NPD |

**UK
CA**

0836

**Colas Ltd, 6210 Bishops Court,
Birmingham Business Park
Solihull, Birmingham B37 7YB**

13

C3 UK 0836-CPR-13/F035

BS EN 13808

Cationic bituminous emulsion

SLX-80 C69BPF2/3/4 C70BPF2/3/4

intended to be used for surface treatment as surface dressings