



0836

**Colas Ltd, 6210 Bishops Court, Birmingham Business Park
Solihull, Birmingham B37 7YB**

13

C1 UK 0836-CPR-13/F035

BS EN 13808*Cationic bituminous emulsion***Surfix C C69BF2/3/4***intended to be used for surface treatment as surface dressings***EMULSION**

- | | |
|----------------------------------------------|-------------------------|
| • Efflux 4 mm at 40°C – EN 12846-1 | 5-100 s (Class 5/6) |
| • Water effect on binder adhesion – EN 13614 | ≥ 90 (Class 3) |
| • Breaking behaviour – EN 13075-1 | < 110-195 (Class 2/3/4) |

RECOVERED BINDER

- | | |
|-----------------------------------|------------------|
| • Penetration at 25°C – EN 1426 | ≤ 330 (Class 7) |
| • Softening point – EN 1427 | ≥ 35°C (Class 8) |
| • Cohesion by pendulum – EN 13588 | NR |

STAGE 1 DURABILITY – STABILISED BINDER

- | | |
|-------------------------------------------------|-----|
| • Durability of penetration at 25°C – EN 1426 | NPD |
| • Durability of softening point – EN 1427 | NPD |
| • Durability of cohesion by pendulum – EN 13588 | NR |

STAGE 2 DURABILITY – AGED BINDER

- | | |
|-------------------------------------------------|------------------|
| • Durability of penetration at 25°C – EN 1426 | ≤ 330 (Class 7) |
| • Durability of softening point – EN 1427 | ≥ 35°C (Class 8) |
| • Durability of cohesion by pendulum – EN 13588 | NR |

Dangerous regulated substances

NPD

**UK
CA**

0836

**Colas Ltd, 6210 Bishops Court, Birmingham Business Park
Solihull, Birmingham B37 7YB**

13

C1 UK 0836-CPR-13/F035

BS EN 13808

Cationic bituminous emulsion

Surfix C C69BF2/3/4

intended to be used for surface treatment as surface dressings