


## UKCA marking information – Colas Ltd

 0836	
<b>Colas Ltd, 6210 Bishops Court,  Birmingham Business Park  Solihull, Birmingham, B37 7YB</b>  17  C16 UK 0836-CPR-13/F035	
<b>BS EN 13808</b> <i>Cationic bituminous emulsion</i>  <b>Colbond Multi – C67BP2/3/4/ C69BP2/3/4</b> <i>intended to be used for surface treatment as bond coat and sealing</i>	
EMULSION	
• Efflux 4 mm at 40°C – EN 12846-1	5-70 s (Class 5)
• Water effect on binder adhesion – EN 13614	NR (Class 0)
• Breaking behaviour – EN 13075-1	≤ 110 - 195 (Class 2/3/4)
RECOVERED BINDER	
• Penetration at 25°C, 0.1 mm – EN 1426	≤ 100 (Class 3)
• Softening point, °C – EN 1427	≥ 50 (Class 4)
• Cohesion by pendulum, J/cm <sup>2</sup> – EN 13588	≥ 1.0 (Class 4)
STAGE 1 DURABILITY - STABILISED BINDER	
• Durability of penetration at 25°C – EN 1426	NPD
• Durability of softening point – EN 1427	NPD
• Durability of cohesion by pendulum – EN 13588	NPD
STAGE 2 DURABILITY - AGED BINDER	
• Durability of penetration at 25°C – EN 1426	≤ 100 (Class 3)
• Durability of softening point – EN 1427	≥ 50 (Class 4)
• Durability of cohesion by pendulum – EN 13588	≥ 0.7 (Class 5)
Dangerous regulated substances	NPD

**UK  
CA**

0836

**Colas Ltd, 6210 Bishops Court,  
Birmingham Business Park  
Solihull, Birmingham, B37 7YB**

**17**

C16 UK 0836-CPR-13/F035

***BS EN 13808***

*Cationic bituminous emulsion*

***Colbond Multi – C67BP2/3/4/ C69BP2/3/4***

*intended to be used for surface treatment as bond coat and sealing*