



0836

**Colas Ltd, 6210 Bishops Court, Birmingham Business Park  
Solihull, Birmingham, B37 7YB**

**13**

C27/1 UK 0836-CPR-13/F035

**BS EN 13808**

Cationic bituminous emulsion

**RS Bitukold for RS Spray – C60B3/4, C65B3/4**

intended to be used for surface treatment as joint sealing in road construction and road maintenance

**EMULSION**

- |  |                    |
|--|--------------------|
| • Efflux 2 mm at 40°C - EN 12846-1           | NR (Class 0)       |
| • Water effect on binder adhesion – EN 13614 | ≥ 90 (Class 3)     |
| • Breaking behaviour – EN 13075-1            | 70-195 (Class 3/4) |

**RECOVERED BINDER**

- |                                   |     |
|-----------------------------------|-----|
| • Penetration at 25°C - EN 1426   | NPD |
| • Softening point – EN 1427       | NPD |
| • Cohesion by pendulum – EN 13588 | NR  |

**STAGE 1 DURABILITY - STABILISED BINDER**

- |   |     |
|---|-----|
| • Durability of penetration at 25°C – EN 1426   | NPD |
| • Durability of softening point – EN 1427       | NPD |
| • Durability of cohesion by pendulum – EN 13588 | NR  |

**STAGE 2 DURABILITY - AGED BINDER**

- |   |     |
|---|-----|
| • Durability of penetration at 25°C – EN 1426   | NPD |
| • Durability of softening point – EN 1427       | NPD |
| • Durability of cohesion by pendulum – EN 13588 | NR  |

Dangerous regulated substances

NPD



0836

**Colas Ltd, 6210 Bishops Court, Birmingham Business Park  
Solihull, Birmingham, B37 7YB**

**13**

C27/1 UK 0836-CPR-13/F035

**BS EN 13808**

Cationic bituminous emulsion

**RS Bitukold for RS Spray – C60B3/4, C65B3/4**

intended to be used for surface treatment as joint sealing in road construction and road maintenance