

COLAS PRODUCTS DATA SHEET

RS BITUKOLD SPRAY



RS Bitukold is a rapid setting, cold applied thixotropic bitumen emulsion designed for sealing vertical joints. The cationic formulation of **RS Bitukold** ensures a rapid set even in cold, damp conditions, with an initial cure taking place within 15 minutes. **RS Bitukold** is mainly used for the protection of new joints in freshly laid asphalt or macadam.

WHERE TO USE?

- Transverse and longitudinal vertical joints
- Trench reinstatements
- Patch repairs
- Drain or manhole frames
- Kerb channels

PREPARATION

Ensure that the surface is clean and free from loose materials, oil, grease, standing water and weeds.

APPLICATION

Shake can vigorously before use. Turn can upside down and apply **RS Bitukold Spray** in even strokes with nozzle 200-300mm away from the surface to be treated. Ensure complete coverage. After use spray briefly with can in upright position to clear nozzle.

COVERAGE

The coverage rate for **RS Bitukold Spray** should be 0.7 – 1.5 kg/m², depending on the texture and porosity of the surface.

PACKAGING

RS Bitukold Spray is supplied in 600ml aerosol cans (12 per box).

STORAGE

- Caution: pressurised container, protect from sunlight
- Do not pierce or burn even after use
- Do not expose to temperatures exceeding 50°C
- Do not spray on a naked flame or any incandescent material
- Keep out of reach of children
- Store in an upright position

STANDARDS

RS Bitukold Spray complies with BS 594987: Clause 6.8 Joints, vertical face coating.

SAFETY

For full safety information, please request the **RS Bitukold Spray** Safety Data Sheet 54 using the contact information below.

NATIONAL SALES OFFICE

Loushers Lane
Warrington
Cheshire
WA4 6RZ
T: 01925 632 616
E: product.sales@colas.co.uk



WE OPEN THE WAY